

Carbon Steel Corrugated Hose and Galvanized Braid

Universal UC3C hose is an industrial weight high quality corrugated hose which is available with a wide variety of fitting possibilities. UC3C is designed for applications which require high pressure ratings and flexibility.

Nominal Inside Dia. (inches)	Part Number	Outside Diameter (inches)	Weight Per Foot (lbs)	Nominal Wall Thickness	Working Pressure (PSIG)	Minimum C Bend Radius	
						Static (inches)	Intermittent (inches)
1/4"	UC3C	0.540	0.187	.011 - .012"	1540	7/8"	5"
	U202C	0.591	0.267		3003		
3/8"	UC3C	0.705	0.306	.011 - .012"	970	1 1/8"	5 1/2"
	U202C	0.756	0.428		1892		
1/2"	UC3C	0.870	0.416	.011 - .012"	800	2"	7"
	U202C	0.921	0.538		1560		
3/4"	UC3C	1.211	0.562	.015 - .016"	600	2 1/8"	8"
	U202C	1.267	0.758		1170		
1"	UC3C	1.531	0.761	.015 - .016"	385	2 3/4"	9"
	U202C	1.587	0.981		751		
1 1/4"	UC3C	1.839	0.976	.015 - .016"	355	3 1/2"	11"
	U202C	1.903	1.270		692		
1 1/2"	UC3C	2.164	1.460	.017 - .018"	315	3 3/4"	12"
	U202C	2.228	1.848		614		
2"	UC3C	2.795	2.507	.017 - .018"	310	5"	15"
	U202C	2.875	3.192		605		
2 1/2"	UC3C	3.260	2.739	.019 - .021"	245	7 3/4"	18"
	U202C	3.340	3.473		478		
3"	UC3C	3.910	3.004	.019 - .021"	155	8 3/4"	22"
	U202C	3.990	3.812		302		

Working pressure is established at 25% of burst pressure.

Maximum service temperature is 850°F.

Galvanized steel braid has been custom designed to match the hose pressure and flexibility requirements.

All hoses are a standard pitch helical design. Not available in annular.

Specifications

Part numbers UC3C are single braided construction, U202C are double braided construction.

If the service conditions exceed 70°F the working pressure rating must be reduced by the following factors;

Temperature (°F)	Multiply By
70	1.00
150	.99
200	.97
250	.96
300	.93
350	.91
400	.87
450	.86
500	.81
600	.74
700	.66
800	.52
900	.50

The maximum service temperature is 850° F.

The working pressure is the maximum unrestrained operating pressure of the hose. It is established as 25% of the burst pressure for braided assemblies. The test pressure should not exceed 150% of the working pressure. All sizes are satisfactory for full vacuum.

The static bend radius is the minimum hose center line radius that the hose can be bent for installation purposes. No additional motions other than vibration can be imposed.

The intermittent bend radius is the minimum hose centerline radius that the hose can be bent for cyclic motions. These motions occur on a slow and constant basis such as thermal expansion.

Where flow velocity exceeds 150 ft/sec gas or 75 ft/sec liquid, a flexible fully interlocked liner should be used.

When the hose is installed in a bent condition, the working pressure should be reduced by 50% for a 90 degree bend, 25% for a 45 degree bend, and so on, proportional to the angle of the bend.

As a broad rule of thumb, pressure drop in a corrugated hose is approximately three times that in steel pipe.

The cycle life expectancy of a metal hose is affected by factors such as: bend radius, operating temperature, operating pressure and materials. Any change in one of these factors will result in a change in the cycle life of the metal hose assembly. Please consult Universal Metal Hose for the best hose recommendation.

The live length is the flexible portion of an assembly, and is used to determine the maximum allowable lateral offset the hose assembly can take. The overall length is calculated by adding the dimensions for the end fitting

Fitting Options


UC3C and U202C can be fitted with a wide variety of end fittings in both similar and dissimilar metals. Consult factory inside sales representative for details.

Testing

All hoses are leak tested at 100 PSIG with air under water. Other testing options are available. Consult factory for details.

Optional Materials

Universal also manufactures helically corrugated hose in Stainless Steel, Bronze, Inconel, and Monel.



Universal Metal Hose

A Hispan Company

17111 South Wallace Street
South Holland, IL 60473-2735
Voice: 773-277-0700
Fax: 773-277-0727
www.universalmetalhose.com